



GAS ENGINE AND GENERAL ACCESSORIES

MOTORTECH COOLANT FILTER

CLEAN YOUR COOLANT WITH OUR FILTRATION UNIT AND PREVENT EQUIPMENT FAILURES

Benefits:

- Easy to install
- Cleans and maintains coolant system from rust and contaminants
- Increases water pump life
- Reduces coolant deposits and increases cylinder head efficiency and life
- Stainless Steel filter elements can be cleaned – NO WASTE
- Visual flow indicator
- Easy to service – decreases maintenance cost
- Filter micron rating:
standard – 50 micron
optional – 25 micron
- Flow rate up to 30 GPM



A COOLANT SHOULD BE CLEAN AND BRIGHT

Technical Advantages:

- Inhibits electro-chemical degradation of engine components. The engine behaves like a big battery when coolant is flowing. Contaminants make it easier for current to flow through the current, which degrades EPDM, buna, rubber, and soft metal or aluminum components (water pump bearings, impellers, etc.)
- Cleaned coolant inhibits corrosion, cavitation and erosion from engine parts like liners, water pump and impellers
- Prevents "flash-off" in the cylinder heads when engine has an emergency stop; as the coolant can properly dissipate thermal loads
- Inhibits scale build-up on all coolant passages and surfaces of the engine



GAS ENGINE AND GENERAL ACCESSORIES

HOW TO ORDER ...

Part No.	Type	Part No.	Type
Coolant Filter Complete		Filterelement	
25.00.009-50	coolant filter, 9", 50 micron	25.00.109-50	filter element, 9", 50 micron
25.00.009-50-30	coolant filter, 9", 50 micron, 30" stand	25.00.109-25	filter element, 9", 25 micron
25.00.009-25	coolant filter, 9", 25 micron	25.00.118-50	filter element, 18", 50 micron
25.00.009-25-30	coolant filter, 9", 25 micron, 30" stand	25.00.118-25	filter element, 18", 25 micron
25.00.018-50	coolant filter, 18", 50 micron		
25.00.018-50-49	coolant filter, 18", 50 micron, 49" stand	Spare Parts	
25.00.018-25	coolant filter, 18", 25 micron	25.00.201	repair kit, flow indicator
25.00.018-25-49	coolant filter, 18", 25 micron, 49" stand	25.00.202	repair kit, gasket


25.00.018-50-49

Coolant Filter

Housing Size
 009 9" Element
 018 18" Element

Filter Rating
 50 micron (standard)
 25 micron (optional)

Stand Options
 30 30" stand
 49 49" stand







25.00.009-50

25.00.018-50

25.00.009-50-30

25.00.018-50-49



Minimum distances required for changing the element, on a unit mount kit.

19.00

Distributed by: